

Farm Stock Turbo

Weights: 10500, 11500, 12500, 14500

1. General rules apply.
2. Must have OEM stock block and head, Driveline/Transmission and sheet metal. Fuel system, frames, hoods, drawbar, grill, seat and front end. No stripping of parts to make weight in a lower class.
3. Speed limit is 10 mph.
4. Weights: Hanging suitcases or homemade weight brackets are allowed. No weights to be hung off the 3-point arms and beyond the rear tire. Must have a 12" of clearance above the hitch.
5. Fuel: Turbo tractors only. 2800 RPM maximum. Turbo must be factory installed. All oil lines, exhaust system and intake tubing must be stock. No water injection is allowed. Stock injection pump. Turbo size is limited to 2.4-inch inlet.
6. Exhaust: No curved straight pipes allowed. Must exit in factory location.
7. PTO, hydraulics must be functional on tractors equipped with such devices

Farm stock – Non-Turbo Rules

1. General rules apply
2. Only factory stock engine blocks and heads allowed. No 800 components in Minneapolis moline's. block, driveline/transmission and sheet metal must be of the same manufacturer. No custom or aluminum frames. Must have factory frames and front end. Fenders are highly recommended. Front weights may not extend further forward than 11" from the centerline of the rear axle.
3. Tractor engine RPM's speed must be controlled by stock throttle lever only. Factory carburetor and stock injection pump, no electric fuel pumps. No down drafts carbs or fuel injections unless OEM. Single updraft carb. No diesel to gas conversions, no homemade manifolds. Exhaust must exit in the original tractor location. Tractor's equipped with a gear reduction starter, pull in the light improved farm class.
4. Press steel rims allowed. No cut or ground tires. No stripping of parts to make weight in a lower class.
5. Engine side shields are not allowed unless originally equipped with OEM. Must be removed for tech inspection if required.
6. Tractors must have working hydraulics and PTO if equipped.
7. Suitcase weights and custom-made weight brackets are allowed.
8. Electronic pickup inside the original distributor housing and stock appearing coils are allowed.